





1 2 3 4 5 6 7 8

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ADT-LINK ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ADT-LINK IS PROHIBITED

版本 REV	变更内容 DESCRIPTION	变更号 ECN No.	日期 DATA
1.0	ISSUE	REL	2025-Aug-20



3D VIEW

FEATURES:
M.2 NVMe to U.2 SFF-8639
Extension Flat CABLE
Specification: PCIE x4

PHYSICAL PROPERTIES:
Operation Temp. Range: -20°C to 80°C
PAIR Cable Flammability rating: None

ELECTRONIC CHARACTERISTICS:
1. Min. Insulation DC Resistance (Mohm.km): 100
2. Dielectric Strength (kV/min): 0.50
3. Max.DC Resistance at 20°C (ohm/km): 376
4. Impedance(Ω) TDR: 85±5(differential)
5. Delay skew(ps/m) Intra: <=10
6. Delay (ns/m): <=5.18



NOTE
1.100% OPEN/SHORT TEST.
2.DIMSION MARK "▼" BY QC CHECK.

K47SF-BK-5cm	50±5
K47SF-BK-10cm	100±5
K47SF-BK-15cm	150±5
K47SF-BK-20cm	200±10
K47SF-BK-30cm	300±10
K47SF-BK-40cm	400±10
K47SF-BK-50cm	500±20
Part-Number	Length (mm)

ADT-LINK

7	Connector	XH 2P 2.54mm Pitch CONNECTOR	1Pcs
6	Tube	Heat shrink tube	1Pcs
5	Connector	U.2 SFF-8639 68Pin Receptacle, Straddle Mount	1Pcs
4	Edge PCB	M.2 NVMe CARD EDGE PCB, Black, with M key, ON GOLD FINGER, UL 94V-0	1Pcs
3	PAD	Aluminum 2.8mm PCB PAD	1Pcs
2	CABLE	10*0.82mm 30AWG*5PAIR CABLE, DIFF 85 Ohm, Black, silver plated copper, FEP insulated	1Pcs
1	CABLE	12*0.82mm 30AWG*6PAIR CABLE, DIFF 85 Ohm, Black, silver plated copper, FEP insulated	1Pcs
No.	PART NO.	DESCRIPTION	Q'TY

TITLE: M.2 NVMe to U.2 SFF-8639 Extension Flat CABLE L=5~100cm		DWG NO.: ADT-K47SF-BK-001	
		CUSTOMER NO.: K47SF-BK-xxxxcm	
		CUSTOMER P/N: K47SF-BK	
	SCALE NONE	UNIT mm	CUS REV. V1.0
			ADT REV. V1.0
			DATE 2025-Aug-20
			SHEET 1/1
DRAWING/制图 Dane		CHECKED/审核 June	
		APPROVED/核准 Taotie	