


PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ADT-LINK ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ADT-LINK IS PROHIBITED

版本 REV	变更内容 DESCRIPTION	变更号 ECN No.	日期 DATA
1.0	ISSUE	REL	2025-Jan-03



FEATURES:
PCIe X4 to U.3 SFF-TA-1001
Adapter
Specification: PCIe 5.0x4

PHYSICAL PROPERTIES:
Operation Temp.Range: -40°C to 80°C
Flammability rating: 94V-0

NOTE
1.100% OPEN/SHORT TEST.
2.DIMSION MARK "▼" BY QC CHECK.



No.	PART NO.	DESCRIPTION	Q'TY
5			
4	Shield	Solid, Full-height, Black Baffle	1Pcs
3	Base	FR4, 2mm PCB BASE	1Pcs
2	Connector	U.3 SFF-TA-1001 68Pin Receptacle,Straddle Mount	1Pcs
1	Edge PCB	PCIe X4 CARD EDGE PCB , Black,ON GOLD FINGER, UL 94V-0	1Pcs

ADT-LINK									
TITLE: PCIe X4 to U.3 SFF-TA-1001 Adapter					DWG NO.: ADT-R27B-001				
					CUSTOMER NO. : R27B-xxxxcm				
					CUSTOMER P/N: R27B				
	SCALE	UNIT	CUS REV.	ADT REV.	DATE	SHEET			
	NONE	mm	1.0	1.0	2025-Jan-03	1/1			
DRAWING/制图 Dane			CHECKED/审核			APPROVED/核准			